

# RT112

## Fast Setting Epoxy Sealant

### *Description*

RT112 is a non-sag, fast setting epoxy sealant, which bonds well to a wide range of materials.

### *Benefits*

- Sets in minutes at room temperature
- Applied as a bead, will not sag even on a vertical surface
- Will bond metals, glass, wood, rubbers and many plastics
- Excellent for gap or crack filling
- Supplied in DuoSyringe for easy application
- 50ml and 200ml sizes available with associated mixing nozzles and dispenser guns

### *Typical Properties*

#### *Curing (measurements at 23°C)*

Work life:	5 – 10 minutes
Time to handling:	15 minutes
Time to full cure:	2 hours

#### *Bond Strength (measurements at 23°C)*

Lap Shear (Al / Al)	20 MPa
Tensile Strength	47 MPa

### *Colour*

Fairly clear as a film, milky white otherwise

### *Related Products*

- RT110 fast setting epoxy adhesive
- RT111 fast setting epoxy adhesive
- RT125 flexible, high performance epoxy adhesive
- TriPatch wraparound epoxy repair system

Typical properties where stated are to be considered as representative of the current production and should not be treated as specifications. While the information presented is believed to be true and reliable, users are advised to conduct sufficient investigations to ensure the suitability of any product for its intended use. IS-Rayfast Ltd cannot accept any responsibility for loss or damage that may result from the use of this information.

#### **IS-Rayfast Ltd**

2 Lydiard Fields, Great Western Way, Swindon, Wiltshire, SN5 8UB, UK

T: +44(0) 1793 616700 | F: +44(0) 1793 644304 | E: [uksales@is-rayfast.com](mailto:uksales@is-rayfast.com) | [www.is-rayfast.com](http://www.is-rayfast.com)