

NEOPRENE SLEEVING | PRE-CUT LENGTHS

INSULATED SLEEVINGS



DESCRIPTION:

Neoprene sleeves are made from highly elastic extruded Neoprene, pre-lubricated as standard. They are particularly useful for binding the ends of braided mains leads into plugs and portable equipment. The sleeves can be stretched 5 times in fitting and 2 times in use. Neoprene sleeves are best applied using the expanding tools. Available in 12 colours for easy identification, diameters range from 1.2mm to 20mm. Custom lengths are available to order.

APPLICATIONS:

It has a very high degree of elasticity making it ideal as a binding sleeve for harnessing and the identification of cable looms.

SPECIFICATION:

COLOUR OPTIONS:	Black, Blue, Brown, Grey, Green, Green/Yellow, Red, Orange, Yellow, White, Pink, Violet.
MATERIAL:	Polychloroprene
SERVICE TEMPERATURE RANGE:	-65°C to 95°C
INTERMITTENT TEMPERATURE:	120°C
VOLUME RESISTIVITY:	10 ¹² Ohm/cm
HARDNESS:	50 Shore A
STRETCH FACTOR:	x5 While Fitted x2 When Fitted
SHELF LIFE:	7 + 3 Years
SPECIFICATION:	BS3858/1 except light fastness. BS3G198 Part 1 Type 1. Def Stan 59-15, Type D2c
RoHS COMPLIANT:	Yes

PART NUMBERS:

PART NO.	LENGTH (MM)	INTERNAL DIA. (MM)	MAX.OD OF CABLE (MM)	PACK QTY
CR12x20 (COLOUR)	20	1.2	2.4	1000
CR15x20 (COLOUR)	20	1.5	3.0	1000
CR20x20 (COLOUR)	20	2.5	4.0	1000
CR30x25 (COLOUR)	25	3.0	6.0	1000
CR50x25 (COLOUR)	25	5.0	10.0	100
CR75x25 (COLOUR)	25	7.5	15.0	100
CR100x25 (COLOUR)	25	10.0	19.8	100
CR150x25 (COLOUR)	25	15.0	30.0	100
CR200x25 (COLOUR)	25	20.0	40.0	100

Tel: +44(0) 1793616700 • Fax: +44(0) 1793 644304
uksales@is-rayfast.com • export@is-rayfast.com

www.is-rayfast.com

2 Lydiard Fields, Swindon, Wiltshire, SN5 8UB

