



This limited fire hazard sleeving is halogen free making it ideal for protecting wire and cables in areas where smoke and fume emissions must be minimised. Supplied in 100 metre continuous reels. Low smoke, low toxicity and zero halogen. The compound meets the requirement of DIN/VDE 2007 AND BS6724.

SPECIFICATION:

COLOUR OPTIONS: Black, Blue, Brown, Green, Yellow, Grey, Red, White
MATERIAL: Halogen-Free, Low Smoke
OPERATING TEMPERATURE: -20°C to +90°C
DENSITY: 1.48
TENSILE STRENGTH: 15MPa
ELONGATION AT BREAK: 163%
VERTICAL BURN TEST PASS: UL 1581
SMOKE DENSITY PASS: ASTM E-662
OXYGEN INDEX: 37% ISO 4589-2
AFTER HEAT AGEING FOR 7 DAYS AT 110°C: Tensile: 16.5MPa Elongation: 140%
STANDARDS: DIN/VDE 0207 BS 6724. Wall Thickness: 0.5mm



PART NUMBERS:

PART NO.	INTERNAL DIA. (mm)	TO COVER CABLE SIZE mm ²	COIL LENGTH (m)
CY 1.5 ZH (COLOUR)	1.5	-	100
CY 2.0 ZH (COLOUR)	2.0	-	100
CY 3.0 ZH (COLOUR)	3.0	0.5 - 0.75	100
CY 4.0 ZH (COLOUR)	4.0	1.5 - 2.5	100
CY 5.0 ZH (COLOUR)	5.0	2.5 - 4.0	100
CY 6.0 ZH (COLOUR)	6.0	6.0	100
CY 8.0 ZH (COLOUR)	8.0	10.0	100
CY 10.0 ZH (COLOUR)	10.0	16.0	100
CY 12.0 ZH (COLOUR)	12.0	35.0	100
CY 15.0 ZH (COLOUR)	15.0	50.0	100

Tel: +44(0) 1793616700 • Fax: +44(0) 1793 644304
 uksales@is-rayfast.com • export@is-rayfast.com

www.is-rayfast.com

2 Lydiard Fields, Swindon, Wiltshire, SN5 8UB

