



Our brass dome top glands offer high quality and total reliability. Suitable for use in plant and automation technologies where exceptional and safe functioning are required. Suitable for high demands, offering excellent strain relief.

SPECIFICATION:

MATERIAL: Brass Nickel Plated

CLAMPING INSERT: Polyamide 6

PROTECTION CLASS: IP68

SEALING RING: Neoprene

TEMPERATURE RANGE: -40°C to +100°C



METRIC GLANDS

PART NO.	THREAD SIZE	TD (HOLE SIZE mm)	TL (LENGTH OF THREAD mm)	FOR CABLE RANGE MIN-MAX Ø (mm)	PACK QTY
EPN 700/M12	M12 x 1.5	12.0	6.0	3.0 - 6.5	1
EPN 700/M12L	M12 x 1.5	12.0	12.0	3.0 - 6.5	1
EPN 700/M16	M16 x 1.5	16.0	7.0	4.0 - 8.0	1
EPN 700/M16L	M16 x 1.5	16.0	12.0	5.0 - 10.0	1
EPN 700/M20	M20 x 1.5	20.0	8.0	6.0 - 12.0	1
EPN 700/M20L	M20 x 1.5	20.0	12.0	6.0 - 12.0	1
EPN 700/M25	M25 x 1.5	25.0	8.0	10.0 - 14.0	1
EPN 700/M25L	M25 x 1.5	25.0	12.0	12.0 - 18.0	1
EPN 700/M32	M32 x 1.5	32.0	9.0	13.0 - 18.0	1
EPN 700/M32L	M32 x 1.5	32.0	15.0	17.0 - 24.0	1
EPN 700/M40	M40 x 1.5	40.0	9.0	18.0 - 25.0	1
EPN 700/M40L	M40 x 1.5	40.0	15.0	22.0 - 32.0	1
EPN 700/M50	M50 x 1.5	50.0	9.0	22.0 - 32.0	1
EPN 700/M50L	M50 x 1.5	50.0	15.0	29.0 - 40.0	1
EPN 700/M63	M63 x 1.5	63.0	14.0	34.0 - 44.0	1
EPN 700/M63L	M63 x 1.5	63.0	18.0	37.0 - 53.0	1

METRIC LOCKNUTS



PART NO.	THREAD SIZE	DEPTH (mm)	PACK QTY
EPN 710/M12	M 12 x 1.5	2.8	1
EPN 710/M16	M 16 x 1.5	3.0	1
EPN 710/M20	M 20 x 1.5	3.5	1
EPN 710/M25	M 25 x 1.5	4.0	1
EPN 710/M32	M 32 x 1.5	5.0	1
EPN 710/M40	M 40 x 1.5	5.0	1
EPN 710/M50	M 50 x 1.5	5.0	1
EPN 710/M63	M 63 x 1.5	5.0	1